

Galigeo for Cognos Analytics Installation Guide - G19.0 - eXperience

Table des matières

Introduction	3
About this document	4
Chapter 1: Pre-requisites	5
1.1 Architecture Schema	6
1.2 Cognos Server	7
1.3 ArcGIS - Optional	9
ArcGIS Server	9
ArcGIS Online	11
1.4 WFS - Optional	11
1.5 Galigeo Server	11
1.6 Network	13
1.7 Client	14
Chapter 2: Installation of Galigeo web application	15
2.1 Global Overview	16
2.2 Where the installation takes place?	16
2.3 Deploy the web application	16
2.4 Tomcat Configuration	17
Memory Configuration	17
Special characters	17
2.5 Font installation	19
2.6 Finalize installation	19
2.7 Frontal Web Server	19
2.8 Cluster deployment	20
Chapter 3: Update an existing installation	21
Chapter 4: Uninstall Galigeo	22
Chapter 5: Galigeo Manager	23
Chapter 6: Insert Maps In Cognos Reports	24
Chapter 6 : Annexes	24
6.1 Backup of Galigeo Home	25

Introduction

In this chapter:

Public concerned by this guide

Document goal

Reading conventions

About this document

PUBLIC CONCERNED BY THIS GUIDE

This document is aimed at technical persons in charge of the preparation and execution of the Galigeo platform installation as well as persons doing the exploitation.

DOCUMENT GOAL

This document presents the technical architecture of the Galigeo Solution. It describes the technical pre-requisites and the installation steps.

Galigeo application is a web service used as a Cognos Analytics Custom Control, a new feature of the IBM Cognos Analytics platform.

READING CONVENTIONS



Steps to follow



Notice



Advice



Carefull



Example

Chapter 1: Pre-requisites

In this chapter:

[Architecture Schema](#)

[Cognos Server](#)

[Galigeo Server](#)

[Network](#)

[Client Machine](#)

1.1 Architecture Schema


GENERAL ARCHITECTURE

Galigeo is designed as an n-tiers, client-server, architecture deployed on Intranet/Internet:

- The top most layer is the “**presentation tier**” or the user interface. The Galigeo user interface is a thin Internet remote client.
- The “**application tier**” or the business logic tier consists of the Cognos Analytics BI server, Galigeo server (and optionally ArcGIS Server). This tier controls the data exchange and connections between the presentation tier and the data tier (described below). **Note that the** Cognos server also controls the authentication/access.
- The last layer is the “**data tier**” with database servers where information is stored in and retrieved from DBMS.

The complete architecture includes the tools for managing and administering this system: The Galigeo Manager module, BusinessObjects Administration and Designer.

ARCHITECTURE SCHEMA FOR THE HTML CLIENT



1.2 Cognos Server

The Cognos server delivers the data for the Cognos reports that will be visualized and analyzed in the Galigeo maps. The maps are embedded into the Cognos reports.

Galigeo does not require to install any additional component on the Cognos server.

Item	Pre-requisite	Notices	Check test
IBM Cognos Analytics: 11.0.8, 11.0.9, 11.0.10, 11.0.11, 11.0.12, 11.0.13	<ul style="list-style-type: none"> New Cognos Analytics HTML5 Portal: Cognos Viewer, Report Studio, Cognos Administration	The old cognos HTML4 portal is not supported as the new Cognos analytics Custom Control Tool is not supported	<p>1st test – Cognos Portal present - launch Cognos Portal URL: Ex : C11: http://cog-srv:9300/bi</p> <p>The Cognos login screen should appear.</p> <p>2nd test – Access to Cognos Viewer – connect to Cognos Portal, open and refresh a Cognos report.</p> <p>3rd test – Access to Report Studio – Cognos Portal > Launch Menu > Report Studio.</p> <p>4th test – Access to Cognos Administration – Cognos Portal > Launch Menu > Cognos Administration.</p>
Cognos User Account	A Cognos user account with the ad hoc permissions is necessary to run the tests. This account is used	Permissions on reports: <ul style="list-style-type: none"> Read Write Execute 	<p><i>See the second test above:</i> Open and refresh a Cognos report.</p>

	as Galigeo advanced user.	<ul style="list-style-type: none">• For report + maps PDF View: Access to capability "Specification Execution"	
--	---------------------------	---	--

1.3 ArcGIS - Optional

Galigeo application that embeds its own geographical data is fully independent and does not need any GIS server.

However, the Galigeo application is able to use data from ArcGIS Server.

ArcGIS Server

The ArcGIS server can be used as a map service and feature service for the Cognos / Galigeo reports.

Galigeo does not require to install any additional component on the ArcGIS server.

Item	Prerequisite	Notices	Check tests
ESRI Products ArcGIS Server	<p>ArcGIS Server 10.1x, 10.2x, 10.3x, 10.4x, 10.5x, 10.6x</p> <p>With the following tools:</p> <ul style="list-style-type: none"> • ArcMap/ArcGIS for Desktop: for creating map projects • ArcGIS Manager to publish and manage map services 	The ArcSDE version is independent with Galigeo.	<p><u>1st test</u> – Check ArcGIS Manager - launch its url:</p> <p>Ex ArcGIS 10 java:</p> <p>http://esri-srv:8099/arcgismanager/main/login.jsf</p> <ul style="list-style-type: none"> - The login screen should display. - Connect with an arcgismanager account and access the map services page
Map Service	<p>ArcGIS Server Map service published from a MXD or a MSD with in particular the options "Export Map" and "Query" (to set during the publishing)</p> <p>The ArcGIS MapServices used by Galigeo must be available via REST from the client machines and also from Galigeo Server machine</p>	<p>The use of MSD format is recommended.</p> <p>Secured MapServices are not supported</p>	<p><u>1st test</u> – Open the REST url:</p> <p>Ex ArcGIS 10:</p> <p>http://esri-srv:8399/arcgis/rest/services</p> <p>The list of available mapservices should be displayed.</p> <p><u>2nd test</u> – Mapservice access via REST - click on a mapservice:</p> <p>Ex of mapservice REST URL:</p> <p>http://esri-gis:8399/arcgis/rest/services/ggoMapService/MapServer</p> <p>The mapservice properties and layers displays.</p>
GIS Database	<p>Not important for Galigeo</p> <p>Galigeo neither accesses directly to the GIS database</p>	All ArcGIS supported formats	NA



The connection to ArcGIS Server is done both through Galigeo Server and the client. **This means that the application server, e.g. Tomcat, and the client (web browser) must see ArcGIS Server.**

ArcGIS Online

Galigeo offers the possibility to connect automatically to ArcGIS Online (AGOL) to use the Drive Time service, for example. The credentials are activated as soon as the appropriate license key is declared in Galigeo Administration console.



The connection to ArcGIS Online is done through Galigeo Server, the one that hosts Galigeo cartographic viewer. **This means that the application server, e.g. Tomcat, must see arcgis.com without any proxy authentication.**

1.4 WFS - Optional

The Open Geospatial Consortium (OGC) **Web Feature Service** (WFS) Interface Standard provides an interface allowing requests for geographical features across the web using platform-independent calls

The OGC membership defined and maintains the WFS specification. Numerous commercial and open-source implementations of the WFS interface standard exist, including the open-source reference implementations GeoServer and deegree.

The WFS support comes has an extension to the product. Only versions 1.0.0 and 2.0.0 are supported. The supported output formats are GML3 or GeoJson.

Adding a WFS layer is done through the Galigeo Manager > Catalog tab > Add a layer then select an url. The specified url must a WFS request of type GetFeature. The returned entities must use the reference system EPSG:4326. For example:

https://data.gov.au/geoserver/ballarat-heritage-area-gutter-rails/wfs?request=GetFeature&typeName=ballarat-heritage-area-gutter-rails:ckan_04fdff50_c07d_4611_8871_2b4a5787de28&outputFormat=application/json&version=1.0.0

Some WFS servers become unstable when they return a large number of result. The maximum number of records can be limited by adding the url the parameter "maxFeatures" for versions 1.0.0 or "count" for versions 2.0.0.

1.5 Galigeo Server

The Galigeo server hosts the Galigeo web module.

Softwares pre-requisites:

Item	Prerequisite	Notices	Check tests
OS	Windows Server 2008, 2012 all editions RedHat Enterprise Linux 5, 6	NA	NA
Java Environment	Java Development Kit (JDK) 1.7.0_xx	NA	<i>1st test (basic): type in a shell command prompt : java -version</i> Example of expected result:

	1.8.0_xx		<p>java version "1.7.0_17" ...</p> <p><i>2nd test: in the application server configuration console, check what Java version is used.</i></p> <p>Ex Tomcat - Check the parameter « Java Virtual Machine » in the tab « Java » of the configuration console:</p> <p>C:\jdk1.7.0_17\jre\bin\server\jvm.dll</p>
Application Server	Tomcat 7.0.x (jdk 1.7) Tomcat 8.0.x (jdk 1.8) Tomcat 8.5.x (jdk 1.8)	NA	<p><i>Go to the application server URL. The version number usually displays:</i></p> <p>Ex Tomcat: http://ggo-srv:8080</p>

We recommend to use a 64 bits Tomcat application server and Java machine.

Minimum and recommended resources sizing for Galigeo Tomcat application server (64 bits):

Component	Minimum	Recommended for 5 concurrent users (concurrent sessions)
Processor #core	Type Intel Xeon 2 cores	Type Intel Xeon 4 cores multithread
Tomcat Memory	2 Go RAM	4 Go RAM
Disk space (Tomcat + Galigeo)	2 Go	10 Go SAS 15k rpm ou SSD



For proper operation of HTML5 Print module, image or PDF, it is important that the Galigeo Server has access to base maps, either on internet or intranet.

1.6 Network

This table lists the ports used for all the modules involved with Galigeo webapp. The ports must be available from the calling application, which might in some cases require some firewall adjustment.



The default port values might be different in the real situation.

Port	Protocol	Opened on	Used by	Default Value	Firewall rule
Galigeo Tomcat port	HTTP(S)	GGO Server	<ul style="list-style-type: none"> - Cognos Client (from Cognos Portal to GGO server as a Cognos Custom Control) - Galigeo Client (from client to GGO server) 	8080	NA
HTTP Port used by the ArcGIS REST services - Optional	HTTP(S)	GIS Server	<ul style="list-style-type: none"> - Galigeo Manager (from GGO server to ArcGIS server) - Galigeo Server to query ArcGIS server mapservice (from Galigeo server to ArcGIS server) - Galigeo client: to query ArcGIS server basemaps if any 	8399	Open in the direction Client → GIS The Galigeo Server must have access to the REST services with the same url as the client.
Access to ArcGIS Online - Optional	HTTPS	arcgis.com	to query ArcGIS Online (from Galigeo server to ArcGIS Online)	443	Open in the direction Galigeo Server → AGOL

1.7 Client

The web browser on the client machine is used to access Cognos HTML5 Portal and the Cognos Reports / Galigeo maps.

Item	Recommended	Notices	Check tests
OS	Windows Seven, 8.1, 10 desktop	NA	NA
HTML5 Client Web browser	Internet Explorer: 11, Edge FireFox: 60 ESR, 64, 65 Chrome: 71, 72	Javascript activated IE compatibility mode is not supported	Go to web browser Menu > About to know its version



For proper operation of Galigeo Application, it is important that the client browser has access to base maps, either on internet or intranet.



Sizing the client machine

- We recommend to use Windows Seven, 8.1 or 10 with 4 to 8 Go of RAM

Chapter 2: Installation of Galigeo web application

In this chapter :

[Global overview](#)

[Where the installation takes place?](#)

[Deploy the web application](#)

[Tomcat Configuration](#)

[Font installation](#)

[Finalize installation](#)

[Frontal Web Server](#)

[Cluster deployment](#)

2.1 Global Overview

Below find a description of the Galigeo web application.

Web Application	Description	Notices
Galigeo.war	Galigeo HTML5 cartographic viewer + print module + Manager	Installation and deployment process takes place at the Galigeo server.

2.2 Where the installation takes place?

The installation takes place on Galigeo server.



The installation steps described in this chapter concern a new installation.

If Galigeo is already installed, see chapter [Update an existing installation](#).

<GGO_PACKAGE> is Galigeo package root directory.



Example of <GGO_PACKAGE> :

\\fileServer\Galigeo4Cognos11_G19.0-eXperience

<GGO_TOMCAT_HOME> is the root directory of Tomcat Server.



Example of <GGO_TOMCAT_HOME> :

Windows: **D:\products\tomcat**

2.3 Deploy the web application

- Stop the Galigeo Tomcat Service
- Go to <GGO_PACKAGE> directory
- Copy **Galigeo.war** webapp to
<GGO_TOMCAT_HOME>/webapps
- Restart Galigeo Tomcat Service.

2.4 Tomcat Configuration

Memory Configuration

In order to get some optimal performances in Galigeo, you need to modify Tomcat's default memory parameters.

Once this change is done, you need to restart Tomcat.

We recommend to use a 64 bits Tomcat application server and Java machine.

Tomcat is installed as a service

- Open the Tomcat configuration console,
- Go to the tab "Java",
- In the area « Java Options » add the two following lines:

-Xrs

-XX:MaxPermSize=256M

- Set the parameter "Initial memory pool" at **128**
- Set the parameter "Maximum memory pool" according to recommendations given in chapter [1.4 Galigeo Server](#)
 - 64 bits Tomcat+JVM example: 4096 (there is no limit for a 64 bits JVM)
 - 32 bits Tomcat+JVM 32 example: 1024 (32 bits JVM is limited to 1536)

Tomcat starts as a script "startup.bat"

- Edit the file **<GGO_TOMCAT_HOME>/bin/catalina.bat**
- At the beginning of the script, add the line:

64 bits Tomcat+JVM example:

```
set JAVA_OPTS=%JAVA_OPTS% -Xmx4096m -Xrs -XX:MaxPermSize=256m
```

32 bits Tomcat+JVM example:

```
set JAVA_OPTS=%JAVA_OPTS% -Xmx1024m -Xrs -XX:MaxPermSize=256m
```

Special characters

To display and print correctly special characters, you need to apply the following settings.

Once changes are done, you need to restart Tomcat.

Add parameter -Dfile.encoding=UTF-8

Tomcat is installed as a service

- Open the Tomcat configuration console,
- Go to the tab "Java",
- In the area « Java Options » add the two following lines:

-Dfile.encoding=UTF-8

Tomcat starts as a script "startup.bat"

- Edit the file **<GGO_TOMCAT_HOME>/bin/catalina.bat**
- At the beginning of the script, add the line:

```
set JAVA_OPTS=%JAVA_OPTS% -Dfile.encoding=UTF-8
```

Add parameter URIEncoding="UTF-8"

- Edit file **<GGO_TOMCAT_HOME>/conf/server.xml**,
- Go to tag **<Connector port="8080"**.. corresponding to Tomcat port (by default 8080), and modify or add the parameter **URIEncoding="UTF-8"**

Example:

```
<Connector port="8080" protocol="HTTP/1.1" connectionTimeout="20000"  
  redirectPort="8443" URIEncoding="UTF-8"/>
```

2.5 Font installation

Installation of the ESRI fonts

The fonts contains a library of symbols used by the thematics.

- Unzip the zip file Tools\font_esri.zip in a folder
- On Windows, select all the .ttf file, right click then choose "Install"
- On Unix / Linux the font installation depends on the distribution

Installation of Windows fonts on Unix / Linux for print module

Windows fonts are used by the HTML5 print module and may be missing on the Unix / Linux server. They need to be installed. This action can be easily accomplished via the native package installer for each Unix / Linux distribution.

For example, for a Debian Linux distribution type (like Ubuntu), the following command needs to be issued:

```
sudo apt-get install ttf-mscorefonts-installer
```

2.6 Finalize installation

- The following operation takes place only once. This operation creates a <GALIGEO_HOME> folder that will be used to store the Galigeo resources. **Galigeo Tomcat user needs to have read/write access to <GALIGEO_HOME> folder.**
- In a browser, launch the following URL: **http(s):// <GGO_TOMCAT_SERVER>:<GGO_TOMCAT_PORT>/Galigeo/**
- Fill the text area with a valid path to <GALIGEO_HOME> folder at Galigeo Server. If the folder does not exist, it is created. Example:

C:\Program Files\Galigeo

- Click on [Continue]

2.7 Frontal Web Server

If Cognos Analytics portal is accessed from client web browsers through a frontal web server, you may want that Galigeo web application is also accessed through this frontal web server.

In such case, Galigeo frontal URL must be declared in [Galigeo Manager](#) console > "Proxy" Menu > "External URL" parameter.



For example, if Cognos portal client URL is:

http://my.organization.com/bi

Then Galigeo client URL could be:

http://my.organization.com/Galigeo

that must be declared in [Galigeo Manager](#) console > "Proxy" Menu > "External URL" parameter

2.8 Cluster deployment

Galigeo can be deployed in a cluster of Tomcat servers that are visible through a unique frontal web server in charge of load balancing and fail-over.



The Territory Management tool, that needs a separate license, does not support cluster deployment.

In a cluster deployment, there is:

- **One Galigeo.war webapp per Tomcat Server**
- **A unique <GALIGEO_HOME> directory shared between all Galigeo webapps.**
 - This can be done, for example, by mounting the same Network Drive, for example "Z:", on each server
 - The path to <GALIGEO_HOME> directory must be the same on each server.
Example: Z:\applications\Galigeo

Installation / configuration steps are detailed below:

NB: We describe below the sharing of a unique <GALIGEO_HOME> directory between all Galigeo webapps by mounting the same Network Drive on each server. There are other ways to do this sharing by using, for example, symbolic links.

- **0 - Prerequisites: on each Tomcat server there is a mount of the same Network Drive,** referencing the same network server.
 - *Example:* **the network drive "Z:"** referencing the same network path, \<NAS_SERVER>\
- **1 - A standard installation is done on each Tomcat server** - see paragraphs 2.2 to 2.6 above - **with a point of attention when finalizing the installation,** see paragraph ["2.6 Finalize installation"](#):
 - **On each Tomcat server the same <GALIGEO_HOME> directory is defined using the network Drive.**
 - *Example:* On each Tomcat server, the path to <GALIGEO_HOME> directory is defined to "Z:\applications\Galigeo"
 - *Remark:* the "real" network path corresponding to the above path is "\<NAS_SERVER>\applications\Galigeo"
- **2 - Declare Galigeo client / frontal URL in Galigeo Manager:** see paragraph ["2.7 Frontal Web Server"](#).

Chapter 3: Update an existing installation

The procedure takes place on the Galigeo server.

A Galigeo webapp is already deployed in the Galigeo Tomcat.

<GGO_TOMCAT_HOME> is the root directory of Tomcat Server.



Example of **<GGO_TOMCAT_HOME>** :

Windows: **D:\products\tomcat**

- Stop Galigeo Tomcat service
- Go to **<GALIGEO_HOME>/config** (ex: D:\products\galigeo\config), and **inactivate current config.json file by renaming it config.json.old**, for example. The new config.json file is automatically generated on the first display of a G18 map. If the old file has been customized (ex: custom basemaps), the customization has to be transferred to the new file
- Go to **<GGO_TOMCAT_HOME>/webapps** (ex: D:\products\tomcat\webapps\), **delete** or **move** in a backup directory outside tomcat the following elements:
 - **Galigeo** folder
 - **Galigeo.war** file
- Copy the new **Galigeo.war webapp** to **<GGO_TOMCAT_HOME>/webapps**
- **Empty Tomcat cache:** go to **<GGO_TOMCAT_HOME>/work/Catalina/localhost/** and remove **Galigeo** folder
- Restart Galigeo Tomcat service.

Chapter 4: Uninstall Galigeo

The procedure takes place on Galigeo Sever.

<GALIGEO_HOME> is the Galigeo installation directory.



Example of <GALIGEO_HOME> :

Windows: **D:\products\galigeo**

Unix / Linux : **/products/galigeo**

<GGO_TOMCAT_HOME> is the root directory of Galigeo Tomcat Server.



Example of <GGO_TOMCAT_HOME> :

Windows: **D:\products\tomcat**

- Stop Galigeo Tomcat service
- **Backup <GALIGEO_HOME> directory and all its content**
- Delete <GALIGEO_HOME> directory
- Go to <GGO_TOMCAT_HOME>/webapps (ex: D:\product\tomcat\webapps\), **delete** the following elements:
 - **Galigeo** folder
 - **Galigeo.war** file
- **Empty Tomcat cache:** remove the directory **Galigeo** located at <GGO_TOMCAT_HOME>/work/Catalina/localhost
- Restart Galigeo Tomcat Service

Chapter 5: Galigeo Manager

Managing Galigeo application ; users, geographical data catalog, license, etc ; is done in Galigeo Manager web administration console. A full description of these steps is found in the UserGuide.Galigeo4eXperience_G1x_en > Chapter 2: Galigeo Manager.

Galigeo Manager URL is the following:

`http://<GGO_TOMCAT_SERVER>:<GGO_TOMCAT_PORT>/Galigeo/`



`http://ggo-srv:8080/Galigeo/`

Chapter 6: Insert Maps In Cognos Reports

The steps to insert Galigeo Maps in Cognos Reports, using Cognos Custom Control Tool, is found in the UserGuide.Galigeo4eXperience_G1x_en > Chapter 3: Map Reports.

Chapter 6 : Annexes

In this chapter:

[Backup of Galigeo Home](#)

6.1 Backup of Galigeo Home

The procedure takes place on Galigeo server.

<GALIGEO_HOME> is the Galigeo installation directory.



Example of <GALIGEO_HOME> :

Windows: **D:\products\galigeo**

Unix / Linux : **/products/galigeo**



Tomcat service is stopped and restarted during backup procedure.

- Stop Galigeo Tomcat service
- **Backup <GALIGEO_HOME> directory and all its content**
- Restart Galigeo Tomcat service